



12m Hire Containers

Exterior dimensions	(L) 12,192mm x (W) 2,438mm x (H) 2,896mm (tolerance of + or - 5mm).
Interior dimensions	(L) 12,032mm x (W) 2,352mm x (H) 2,698mm (tolerance of + or - 5mm).
Lifting	Full or empty, either (a) at the top corner fittings vertically by means of spreaders fitted with hooks, shackles or twist locks, or (b) at the bottom corner fittings using slings with appropriate terminal fittings at slings angle of thirty (30°) degree to horizontal.
Internal cubic capacity	76.4 cu/m.
Door dimensions	(W) 2,340mm x (H) 2,585mm.
Ratings	Max gross weight 32,500 kilos; Tare weight 3,860 kilos.
Floors	Hardwood plywood or bamboo.
Securing	Each internal corner post is fitted with three lashing bars. Forty lashing rings are fitted, ten on each bottom and top rails.
Ventilators	Four ventilators are affixed, two on each side wall.
Lock Box	A lock box is fitted to the doors (optional).
Colour	Containers are painted brown (RAL 3009) and grey inside (RAL7035). Paint coating consists of 30 microns of epoxy zinc rich primer, 40 microns of epoxy middle coat and 40 microns of acrylic top coat. The underside is coated with 30 microns zinc rich primer and 200 microns of bituminous undercoating.
Testing	All containers are checked on the production line for dimensions, door operation, quality of construction and water tightness.
General construction	Corrosion resistant corten steel construction. Four high strength corner posts fitted with corner castings top and bottom, with interconnecting rails of high tensile steel, with corrugated steel side panels, roof panel and front wall. Two pressed steel doors at rear of container, opening 270 degrees, with four hot dip galvanised locking bars, and fitted with watertight rubber seals.

